



Lyden Oil Company

ProGuard

Product Information

ProGuard Full Synthetic 0W-20

ProGuard Full Synthetic Passenger Car Motor Oil 0W-20 is made from synthetic base stocks for better fuel economy and reduced harmful emissions using advanced detergent-dispersant, antioxidant, anti-wear agent, friction modifier, and defoamant additives for better wear protection. This oil provides excellent protection against sludge, engine rust and corrosion, resist oil thickening by providing enhanced oxidation control under severe service conditions and low temperature operating conditions.

ProGuard Full Synthetic Passenger Car Motor Oil 0W-20 is suitable for use in all seasons in all makes and models of gasoline engines requiring an API specification SN Plus or ILSAC GF-5, 0W-20 viscosity engine oil, including vehicles manufactured by Ford, Chrysler, Honda, Acura, Subaru, Mitsubishi, Hyundai, and Kia .

Typical Properties

ProGuard

Full Synthetic Passenger Car Motor Oil

	0W-20
Product Code Number	504161
Viscosity, ASTM D-445	
cSt at 100 °C	8.2
cSt at 40 °C	43.4
Viscosity Index	166
Cold Cranking Viscosity, ASTM D-5293	
cP at Temp °C	5,800 at -35
NOACK Volatility, % wt. loss, ASTM D-5800	13.9
High Temp/High Shear Visc., ASTD D-4683	
cP at 150 °C	2.7
Pour Point, °C (°F), ASTM D-5950	-51 (-59)
Maximum API / ILSAC Performance	SN+/GF-5

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com